



Wall mounted unit

FTXTP-K + RXTP-N9

comfora



Guaranteed operation down to -25°C



Energy saving during standby mode



Online controller via app

Wall mounted unit providing high efficiency and comfort

- › Guaranteed heating capacity down to -25°C
- › Ideal for above door installation
- › Full range A++
- › Online controller (optional)
- › Space saving contemporary wall mounted design
- › Bluevolution range: lower environmental impact
- › Improved defrost technology resulting in lower running costs
- › Developed for regions with severe winter conditions

FTXTP-K + RXTP-N9



Efficiency data		FTXTP + RXTP	25K + 25N9	35K + 35N9	
Cooling capacity	Min./Nom./Max.	kW	0.70/2.50/4.00	0.70/3.50/4.40	
Heating capacity	Min./Nom./Max.	kW	0.80/3.20/6.20	0.80/4.00/6.70	
Power input	Cooling	Nom.	0.57	0.92	
	Heating	Nom.	0.65	0.90	
Space cooling	Energy efficiency class		A++		
	Capacity	Pdesign	kW	2.50	3.50
	SEER			7.10	7.20
	Annual energy consumption		kWh/a	123	170
Space heating (Average climate)	Energy efficiency class		A++		
	Capacity	Pdesign	kW	2.50	3.00
	SCOP/A			4.98	4.81
	Annual energy consumption		kWh/a	703	873
Space heating (Cold climate)	Energy efficiency class		A		
	Capacity	Pdesign	kW	3.70	4.40
	Annual energy consumption		kWh/a	1,939	2,429
	SCOP/C			3.95	3.80
Nominal efficiency	EER		4.40	3.80	
	COP		4.95	4.44	
	Annual energy consumption		kWh	284	461
	Energy labeling Directive	Cooling/Heating		A/A	

See separate drawing for operation range | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m.


Indoor unit		FTXTP	25K	35K
Dimensions	Unit	HeightxWidthxDepth	mm	
			285x770x225	
Weight	Unit		kg	
			9.0	
Air filter	Type		Removable / washable	
Fan	Air flow	Cooling	m³/min	
	rate	Silent operation/Low/	4.3/5.3/7.7/10.6	
	Heating	Silent operation/Low/	m³/min	
			4.9/5.8/8.0/11.2	
Sound power level	Cooling		dBA	
			58	
	Heating		dBA	
			58	
Sound pressure level	Cooling	Silent operation/Low/High	dBA	
			21/26/43	
	Heating	Silent operation/Low/High	dBA	
			21/26/43	
Control systems	Infrared remote control		ARC480A11	
	Wired remote control		BRC944B2 / BRC073A1	

See separate drawing for electrical data

Outdoor unit		RXTP	25N9	35N9	
Dimensions	Unit	HeightxWidthxDepth	mm		
			551x763x312		
Weight	Unit		kg		
			38		
Sound power level	Cooling		dBA		
			61		
	Heating		dBA		
			61		
Sound pressure level	Cooling	Nom.	dBA		
			48		
	Heating	Nom.	dBA		
			49		
Operation range	Cooling	Ambient	Min.~Max.	°CDB	
				-10~46	
	Heating	Ambient	Min.~Max.	°CWB	
				-25~18	
Refrigerant	Type		R-32		
	GWP		675		
	Charge	kg/TCO2Eq	1.1/0.75		
Piping connections	Liquid	OD	mm		
			635		
	Gas	OD	mm		
			9.50		
	Piping length	OU - IU	Max.	m	
			20		
	Additional refrigerant charge		kg/m		
			0.02 (for piping length exceeding 10m)		
	Level difference	IU - OU	Max.	m	
			15		
Power supply	Phase/Frequency/Voltage		Hz/V		
			1~/50/220-240		
Current - 50Hz	Maximum fuse amps (MFA)		A		
			-		

See separate drawing for electrical data | See separate drawing for operation range | Contains fluorinated greenhouse gases

Daikin Europe N.V. 0 · goliat.d@daikineurope.com · 0 0 · Poland · 0 · 0 · 0 (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

08/2019

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

